



AIR PUMPS

- High strength reinforced aluminum alloy reservoir is lightweight and corrosion resistant
- Pressure relief valve for overload protection
- Suggested air pressure range: 90-175 psi / 6-12 bar
- Designed to be used with single acting cylinders
- Dust cover protection for the release control valve
- Dual stage release control valve
- 5AS200 offers a turbo function that features high flow at high pressure condition
- 5AD150M offers a 4-way control valve for operation of double acting cylinders
- Maximum working pressure: 10,000 psi / 700 bar



5AD150M



5AS150L



5AS200

AIR PUMP SPECIFICATIONS

Used with Cylinder	Usable Oil Capacity (in ³)	Product Code	Pressure Rating (psi)	Oil Output Flow Rate (in ³ /min)		Input Air Pressure Range (psi)	Dimensions (in)				
				No Load	Load		A	B	C	D	E
Single Acting	36.6	5AS60	10,000	61	9	100-200	16.54	9.84	7.01	6.18	5.59
	91.5	5AS150		66	11		10.35	5.00	7.28	5.16	5.35
	122.1	5AS200		65	12		11.57	6.02	7.91	6.18	5.98
	231.9	5AS380		65	11		12.64	5.08	7.36	5.24	7.36
	91.5	5AS150L		61	10		10.98	6.30	8.03	5.12	5.35
	231.9	5AS380L		61	10		12.64	6.42	8.15	5.20	7.36
Double Acting	91.5	5AD150M	10,000	66	11	100-200	10.35	5.00	7.99	5.35	5.35

